



The future of mobility is here.

Jazzy[®] air

E M P O W E R S

The Jazzy Air[®] is a new era in power mobility. Whether at home, or out on the town, the unique appeal of Jazzy Air will elevate your independence and social confidence in style.

- Elevate up to 10 inches in 16 seconds
- Enjoy face-to-face social engagement
- Safely drive elevated at walking speed (3.5 mph)




pridemobility.com

Specifications

| | |
|--|--|
| Weight Capacity | 300 lbs. |
| Maximum Speed¹ | Up to 4.0 mph (non-elevated position) Up to 3.5 mph (elevated position) |
| Ground Clearance² | 2.5" at footplate 1.00" at motor bracket |
| High-Back Seat to Floor Range | 23" - 33" |
| Turning Radius² | 22.5" |
| Overall Size^{2,6} | Length: 42.23" with foot rigging; 38.5" w/out foot rigging Width: 23.4" at the wheels 25.5" with armrests |
| Drive Controller | PG VR2 |
| Drive Wheels | 10" flat free |
| Caster Wheels | 6" solid caster |
| Suspension | Active-Trac [®] with Mid-Wheel 6 [®] Technology |
| Range^{1,4} | Up to 15 miles w/ U1 batteries Up to 18.4 miles w/ 40 Ah batteries |
| Component Weights⁵ | Base: 225 lbs. w/ U1 batteries 245 lbs. w/ 40 Ah batteries U1 Batteries: 25 lbs. 40 Ah Batteries: 32.2 lbs. |
| Drivetrain | Two motor, Mid-Wheel 6 [®] drive |
| Brakes | "Intelligent Braking" (electronic regenerative, disc park brakes) |
| Batteries³ | (2) 12 V, U1 (2) 40 Ah |
| Battery Charger | 3.5 amp, off-board |
| Max. Allowable Incline | 6° |
| Max. Angle Capacity | 6° |
| Maximum Obstacle Climbing Ability | Lowered Position: 2.2" Elevated Position: 1.8" |
| Warranty | 5 year limited (frame) 13 month limited (electronics) 13 month (drive motors) |

- 1) Varies with base model, user weight, terrain type, battery amp hour rating (Ah), battery charge, battery condition, motors, controller type, tire type, and tire condition. This specification is subject to a variance of +10%, -5%.
- 2) Due to manufacturing tolerances and continued product improvement, this specification can be subject to a variance of (+ or -) 3%.
- 3) AGM or Gel-Cell type required. See VI. "Batteries and Charging."
- 4) Tested in accordance with ANSI/RESNA, WC Vol. 2, Section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.
- 5) Battery weight may vary based on manufacturer.
- 6) Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.

NOTE: This product conforms to all applicable ANSI/RESNA, ISO 7176 Series, and EN12184 standards. All specifications subject to change without notice.



Find a compatible lift for your vehicle online:
PRIDEMOBILITY.COM/LIFT-FINDER

10-10-17

Features

- Achieve 10" of power adjustable seat height in 16 seconds
- Elevate or lower seat height while on the move with the "Air" button or PG VR2 joystick drive controller
- Seat and integrated footplate design provides maximum comfort in both elevated and non-elevated positions
- Angle adjustable footplate with three height adjustments
- Choice of 16" x 16"-18" depth adjustable, high-back, reclining sport seat
- Choice of 18" x 18"-20" or 20" x 20"-22" depth adjustable, fold-flat, high-back reclining sport seat
- Choice of 16" x 16"-18", 18" x 18"-20" and 20" x 20"-22" fold-flat solid seat pan
- Angle, height and depth adjustable armrest
- Bright LED marker lights
- 60" lap belt

Colors



Authorized Pride[®] Provider

(US) 800-800-8586 • (CAN) 888-570-1113 • pridemobility.com

Accessories

- Rear basket
- Weather cover
- Cup holder
- Flag kit
- Cell phone holder
- Cane holder
- Walker holder
- Oxygen holder
- Saddle bag
- Replacement shroud (ten available colors)
- Alternative size lap belt: 50", 70", 80", 90"
- XLR USB Charger

Options

- 40 amp AGM batteries
- Swing-away joystick
- Synergy[®] Cushions
 - Solution[®]
 - Solution[®] 1
 - Spectrum[®] Gel
 - Spectrum[®] Foam